

TL220 is powerful versatile and indispensable centrifuge for routine laboratories. It is not only ideal for small laboratory; it can be also very useful in medium and large laboratories. It is high performance motor, **Maintenance free, Brushless and Microprocessor** for preselecting of speed and time.

- Easy entry of key pad
- Easy to read, digital display
- Display of correct speed & time volume
- Impulse key for short centrifuge
- Running time in minute, max 99 min
- Open lid key
- Lid locking
- Motor over heating protection



| MODEL | TH 220 | | TH200 | |
|-------------------|-------------------|--------------|-------------------|--------------|
| Max Speed | 16000r/min | | 16000 r/min | |
| Max RCF | 23669Xg | | 17800xg | |
| Timer Range | 0~99min | | 0~99min | |
| Power Supply | AC220V50Hz5A | | AC220V50Hz5A | |
| Dimensions(LxWxH) | 330x420x275mm | | 230x310x240mm | |
| Weight | 20kg | | 15kg | |
| | Max Speed (r/min) | MaxRCF (xg) | Max Speed (r/min) | MaxRCF (xg) |
| 12x1.5/2.2ml | 16000 | 17800 | 16000 | 17800 |
| 18x1.5/2.2ml | ---- | ---- | 13200 | 16110 |
| 24x1.5/2.2ml | 13200 | 16110 | 13200 | 16110 |
| 36x0.5ml | 16000 | 23669 | 13200 | 16110 |
| 10x5ml | 13000 | 11400 | 13000 | 11400 |
| 12x10ml | 12000 | 14800 | | |
| 6x50ml | 12000 | 13000 | | |