



#### Extended Range pH/ORP/Temperature Meter

The **Mi106** multi parameter portable meter is ideal for field measurements.

The included combined pH/ORP electrode has a built-in temperature sensor and amplifier to prevent electrical interference.

The large display shows readings in an extended range from -2.00 to 16.00 pH or ±2000 mV and simultaneously shows temperature from -5.0 to 105.0°C or 23 to 221°F.

The **Mi106** has a stability indicator and hold feature that freezes the display for easy and accurate recording.

The large display also has graphic symbols to guide you through all operations.

When switched ON it performs a self-check and displays the percentage of the remaining battery level to assure proper working condition.

Calibration is performed automatically at 1 or 2 points using standard (pH 4.01, 7.01, 10.01) or NIST buffers (pH 4.01, 6.86, 9.18).



- Years warranty **3**
- ATC
- Points **2**
- Dual Display
- Self diagnosis
- CE



Specifications	Mi106
Range (*)	pH -2.00 to 16.00 pH mV -2000 to +2000 mV Temp -5.0 to 105.0°C / 23.0 to 221.0°F
Resolution	pH 0.01 pH mV 1 mV Temp 0.1°C / 0.1°F
Accuracy (@25°C)	pH ±0.02 pH mV ±2 mV Temp ±0.5°C up to 60°C; ±1°C outside / ±1°F up to 140°F; ±2°F outside
Typical EMC Deviation	pH ±0.02 pH mV ±2 mV Temp ±0.2°C / ±0.4°C
Temperature Compensation	automatic, from -5 to 80°C / 23 to 176°F
pH Calibration	automatic, 1 or 2 points with 2 sets of memorized buffers (pH 4.01, 7.01, 10.01 or 4.01, 6.86, 9.18)
ORP Calibration	factory calibrated
Probe	<b>MA923D/1</b> , amplified pH/ORP/temperature probe (included)
Environment	0 to 50°C / 32 to 122°F; max RH 95%
Battery Type	1 x 9V alkaline (included)
Battery Life	approx. 500 hours of use
Auto-off	after 8 minutes of non-use
Dimensions	200 x 85 x 50 mm
Weight	260 g (with battery)

(\*) The temperature range is limited to 80°C (176°F) if using the MA923D/1 probe.

#### Accessories

- MA923D/1** Combination amplified pH/ORP/Temp probe with DIN connector and 1 m cable
- M10000B** Electrode rinse solution, 20 mL sachet (25 pcs)
- M10004B** pH 4.01 buffer solution 20 mL sachet (25 pcs)
- M10007B** pH 7.01 buffer solution 20 mL sachet (25 pcs)

- M10010B** pH 10.01 buffer solution 20 mL sachet (25 pcs)
- MA9004** pH 4.01 buffer solution, 230 mL bottle
- MA9007** pH 7.01 buffer solution, 230 mL bottle
- MA9015** Electrode storage solution, 230 mL
- MA9016** Electrode cleaning solution, 230 mL



#### Hard Carrying Case

Each meter is supplied in a hard carrying case ideal for field measurements.



#### Ordering Information

**Mi106** is supplied complete with MA923D/1 pH/ORP/Temp amplified probe with 1 meter cable, 20 mL pH 4.01 and 7.01 sachet of calibration solution, 2x20 mL sachet of electrode cleaning solutions, 9V battery, instructions, all in a rugged carrying case.